



Global® FB 2600 UTC Series – Flatbed coverstitch machines

TECHNICAL SPECIFICATIONS

Machine speed*

6000 spm

Stitch type

602 or 605

Number of needles

2 or 3

Needle gauges

4.8 - 5.6 - 6.4 mm

$\frac{3}{16}$ - $\frac{7}{32}$ - $\frac{1}{4}$ inch

Feed type

differential feed

Differential ratio

1:03 - 1:2.9

Stitch length

min. 1.4 mm - $\frac{3}{64}$ inch

max. 3.6 mm - $\frac{9}{64}$ inch

Presser foot lift

up to 7 mm - $\frac{9}{32}$ inch

Needle type

UY 128 Gas

Bed type

flatbed

FB 2602/FB 2603 UTC – High speed, top and bottomcover chainstitch flatbed machines, fully automatic lubrication and differential feed. Equipped with a lower and upper thread trimmer and presser foot lift (all pneumatic).

MÁQUINAS RECUBRIDORAS

FB 2602/FB 2603 UTC – Alta Velocidad, máquinas recubridora superior e inferior de base plana. Lubricación completamente automática y arrastre diferencial. Equipada con corta-hilos para el hilo superior e inferior y alza-prensatelas (todo neumático).

ÜBERDECKNAHT-MASCHINE

FB 2602/FB 2603 UTC – Hochleistungs- Ober- und Unterüberdecknaht- Flachbett Kettenstichmaschinen. Vollautomatisch geschmiert und differential-Transport. Ausgerüstet mit einem Ober- und Unterfadenabschneider sowie Druckerfußlüftung (alle pneumatisch).

MACHINE RECOUVREMENT BASE PLANE

FB 2602/FB 2603 UTC – Machine point de chaînette à base plane à grande vitesse. Recouvrement inférieur et supérieur. Lubrification automatique et griffe différentielle. Equipée avec coupe-fils inférieur et supérieur et relevage du pied presseur (tout pneumatique).

Global® FB 2600 UTC Series

The Global® FB 2600 UTC series are high quality 2 or 3 needle flat bed machines with top and bottom cover stitch and improved differential feed mechanism.

These machines are equipped with a lower and upper thread trimmer and presser foot lift (all pneumatic).



Pneumatic thread trimming and presser foot device



Upper threadtrimmer

Some features of the Global® FB 2600 Series

- swing-up type looper for easy threading
- fully automatic lubrication
- high quality precision parts
- interchangeable oil-filter
- high speed: up to 6000 spm
- vibration free

Specifications

model	number of needles	number of threads	needle distance			outside stitch length mm	differential feed ratio mm	presser foot lift	needle system	max. sewing speed*
			4.8 3/16	5.6 7/32	6.4 1/4					
FB 2602 UTC	2	4	●	—	—	1.4 - 3.6	1:03 - 1:2.9	7	UY128GAS	6000
FB 2603 UTC	3	5	—	●	—	1.4 - 3.6	1:03 - 1:2.9	7	UY128GAS	6000
FB 2603 UTC	3	5	—	—	●	1.4 - 3.6	1:03 - 1:2.9	7	UY128GAS	6000

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL® Selection is brought to you by:

GLOBAL® is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:

- ① machine model
- ② part numbers