

OV 604-050

Global® OV 604 Series – Single needle overlock machines

TECHNICAL SPECIFICATIONS

Machine speed*
up to 7000 spm

Stitch type
504

Number of needles
1

Stitch length
up to 4 mm

Feedtype
differential feed

Presser foot lift
up to 7 mm

Overedge bight
2 to 5 mm

Needle type
B-27

Number of threads
3

OV 604 - High speed, 3 thread, single needle overlock machines with fully automatic lubrication and external differential feed setting for intermittent gathering.

The 604-class is available in the following varieties and with the following attachments:

- blindhemming device
- ruffler device
- backlatch attachment
- metering device
- vacuum chaincutter

MÁQUINAS REMATADORAS

OV 604 - Máquina overlock de 1 aguja y 3 hilos, alta velocidad, lubricación automática con transporte diferencial. La serie 604 esta disponible con los siguientes dispositivos:

- dobladillados con putada invisible
- fruncidor
- dispositivo de atacado
- alimentador de goma superior (Zeromax)
- cortador de cadenta

ÜBERWENTLUNG-NÄHMASCHINE

OV 604 - Hochleistungs - Einnadel - Dreifaden - Überwindlung Nähmaschinen mit vollautomatischer Schmierung und aussen liegender Differential Schnelverstellung - Verstellung für das intermittierende Kräuseln. Die Klasse 604 ist verfügbar in folgenden Ausführungen und Einrichtungen:

- Blindsticheinrichtung
- autom. Bandzuführung
- Kräuseleinrichtung
- automatischer Kettentrenner
- Kettenklemme

SURJETEUSES

OV 604 - Surjeteuses raseuse à grande vitesse, 1 aiguille - 3 fils, avec lubrification entièrement automatique et griffe différentielle réglable de l'extérieur pour opérations de fronçage. La classe 604 est disponible dans les versions ci - après et avec les équipements suivants:

- Equipement ourleur point invisible
- Retrée de chaînette
- Dispositif d' alimentation supérieure
- Dispositif fronçeur
- Coupe chaînette pneumatique.

Global® OV 604 Series High speed 1-needle 3-thread overlock machines

Easy-to-operate, high speed sewing machines capable of dealing with virtually all kinds of materials and threads to respond to the diverse requirements of the fashion industry. All types and models of the Global® OV 604 series are equipped with a differential feed adjusting mechanism.


















OV 604-000
3-thread blind hemmer



OV 604-057
3-thread with metering device



OV 604-050-BL
3-thread hemmer with manual back latch

model		 number of needles	 number of threads	 needle distance mm	 overedging (mm) width overal width		 stitch length mm	 differential feed ratio	 presser foot lift mm	 max. sewing speed*
OV 604-000		1	3	—	—	—	4	1:0.7 - 1:2	6	7000
OV 604-010		1	3	—	2	2	4	1:0.7 - 1:2	6	6500
OV 604-050		1	3	—	5	5	4	1:0.7 - 1:2	7	6500
OV 604-050-BL		1	3	—	5	5	4	1:0.7 - 1:2	6	6500
OV 604-057		1	3	—	5	5	4	1:0.7 - 1:2	7	6000
OV 604-059		1	3	—	5	5	4	1:1 - 1:3	5	6000

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL® Selection is brought to you by:

GLOBAL® is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:

- ① machine model
- ② part numbers