

SUNSHINE® 3400 Series – Multi needle, double chainstitch flatbed machines with rear puller

TECHNICAL SPECIFICATIONS

Machine speed*
up to 4500 spm

Stitch type
401

Number of needles
4 - 12

Feed type
drop feed

Stitch length
1.5 - 3.6 mm
2.2 - 5.2 mm

Presser foot lift
12 mm

Needle type
UY 113 GS

3404 - Four needle, double chainstitch, flatbed machines. A rear puller is featured on this machine for smooth sewing operations.

3406/3412 - Multi needle, double chainstitch machines. A wide range of available gauges. Combined with front and rear puller make these machines ideal for special operations.

MAQUINAS DOBLE CADENETA CON PULLER DE BASE PLANA

3404 - Maquina de 4 agujas cadeneta doble, de base plana con puller para trabajos mas delicados.

3406/3412 - Maquina de multiples agujas y cadeneta doble, con base plana. Una amplia gama de distancias de agujas distintas se puede pedir igual que varios modelos de embudos. El puller y/o alimentación de goma hace que la maquina es perfecta para trabajos especiales.

DOPPELKETTENSTICH-MASCHINE

3404 - 4 Nadel Doppelkettstich-Flachbettmaschine mit Puller

3406/3412 - 6 Nadel bzw. 12 Nadel Doppelkettstich-Flachbettmaschine mit Puller. Diese Maschinen bieten große Variationsmöglichkeiten durch verschiedene Nadelabstände; Nadelabstand von Nadel zu Nadel 4,8 mm bzw. 6,4 mm.

MACHINES DOUBLE POINT DE CHAINETTE AVEC PULLER ARRIERE

3404 - Machine base plane 4 aiguilles à double point de chainette. La présence du puller arrière assure à cette machine une couture régulière.

3406/3412 - Machines base plane multi-aiguilles. Une gamme complète d'écartements disponibles et de guides combinés avec puller arrière et alimenteur frontal rendent ces machines idéales pour les opérations spéciales.

MACCHINA MULTI-AGHI - CATENELLA DOPPIA CON PULLER

3404 - Macchina a base piana 4 aghi, catenella doppia, con puller posteriore. Adatta per orlare inserendo un elastico all'interno dell'orlo o applicandolo all'esterno.

3406/3412 - Macchina a base piana multi-aghi, catenella doppia. La vasta gamma di aghi disponibili, le misure, le guide, il puller e l'alimentatore rendono queste macchine le piu'adatte a qualsiasi lavorazione particolare.

Sunshine® 3400 Series

High speed multi needle chainstitch machines with rear puller for elastic inserting and other specialized usages. The Sunshine 3400 machines are equipped with an automatic lubrication system.



MD = Metering Device (puller width = 50 mm)



Sunshine 3404 Series




4 needle chainstitch for inserting elastics on boxer shorts, jogging suits etc.


model	number of needles	number threads	needle distance (mm)	stitch length (mm)	needle system	max sewing speed ★
3404 P puller	4	8	25.4 (6.4)	1.5 - 3.6	UY 113 GAS	4500
3404 PMD puller-metering device	4	8	25.4 (6.4)	1.5 - 3.6	UY 113 GAS	4200
3404 PMD puller-metering device	4	8	28.2 (7.2)	1.5 - 3.6	UY 113 GAS	4200
3404 PMD puller-metering device	4	8	31.8 (8.0)	1.5 - 3.6	UY 113 GAS	4200
3404 PMD puller-metering device	4	8	40.0 (10)	1.5 - 3.6	UY 113 GAS	4200

Multi-needle machines conveniently used in a wide variety of applications. A rear puller is also featured on these machines for smooth sewing operations.


Sunshine 3406 - 3412 Series



PPT=puller-pin tuck



PS=puller-shirring



PTA=puller-tape attaching

model	number of needles	number threads	needle distance (mm)	stitch length (mm)	needle system	max sewing speed ★
3406 PTA puller+tape attaching	6	12	32.0 (6.4)	1.5 - 3.6	UY 113 GAS	3800
3408 PMD puller+metering device	8	16	44.8 (6.4)	1.5 - 3.6	UY 113 GAS	3800
3410 P puller	10	20	43.2 (4.8)	1.5 - 3.6	UY 113 GAS	4000
3410 P puller	10	20	57.6 (6.4)	1.5 - 3.6	UY 113 GAS	4000
3410 PMD puller+metering device	10	20	57.6 (6.4)	1.5 - 3.6	UY 113 GAS	3800
3412 P puller	12	24	52.8 (4.8)	2.2 - 5.2	UY 113 GAS	4000
3412 PS puller-shirring	12	24	52.8 (4.8)	2.2 - 5.2	UY 113 GAS	3800
3412 PS puller-shirring	12	24	70.4 (6.4)	2.2 - 5.2	UY 113 GAS	3800
3412 PTA puller+tape attaching	12	24	52.8 (4.8)	2.2 - 5.2	UY 113 GAS	3800
3412 PTA puller+tape attaching	12	24	70.4 (6.4)	2.2 - 5.2	UY 113 GAS	3800
3412 PMD puller+metering device	12	24	52.8 (4.8)	2.2 - 5.2	UY 113 GAS	3800
3412 PMD puller+metering device	12	24	70.4 (6.4)	2.2 - 5.2	UY 113 GAS	3800

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL® Selection is brought to you by:

GLOBAL® is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:

- ① machine model
- ② part numbers