



Global® WF 904/905 Series – Extra heavy duty walking foot machines

TECHNICAL SPECIFICATIONS

Machine speed*	up to 800 spm
Oiling system	semi automatic
Feed type	needle feed walking foot
Presser foot lift	by hand 13 mm by knee 20 mm
Stitch length	WF 904 up to 15 mm WF 905 up to 11 mm
Needle bar stroke	56 mm
Needle type	794 H
Stitch type	301

WF 904/905 – extra heavy duty, single needle, needle feed, walking foot machines equipped with large barrel shuttle hook and reverse.

WF 905-95 – extra heavy duty, long cylinder arm, needle feed, walking foot machine equipped with large barrel shuttle hook and reverse. Extra heavy duty stand available.

MÁQUINAS DE TRIPLE ARRASTRE PARA TRABAJOS EXTRA PESADOS

WF 904/905 – Máquina de una aguja, triple arrastre extra pesada, equipada con garfio grande tipo "barrel" y retroceso.

WF 905-95 – Máquina cilíndrica de brazo largo, triple arrastre extra pesada, equipado con garfio grande tipo "barrel" y retroceso. Disponible con bancada especial reforzada.

DREIFACHTRANSPORTMASCHINEN FÜR EXTREM SCHWERE BEANSPRUGUNG

WF 904/905 – Industrienähmaschine für extrem schwere Beanspruchung. Einnadel-Nadeltransportmaschine mit alternierendem Obertransport. Ausgestattet mit großem Barrelschiffchen. Mit Rückwärtshebel.

WF 905-95 - Industrienähmaschine für extrem schwere Beanspruchung, mit langem Zylinderarm. Nadeltransportmaschine mit alternierendem Obertransport. Ausgestattet mit großem Barrelschiffchen. Mit Rückwärtshebel. Spezialgestelle für besonders schwere Maschinen sind erhältlich.

MACHINE TRIPLE ENTRAÎNEMENT, POUR TRAVAUX TRÈS LOURDS

WF904/905 – Machine pour travaux très lourds, 1 aiguilles, triple entraînement avec navette barrel et marche arrière.

WF 905-95 – Machine pour travaux très lourds, canon avec grand passage sous le bras, triple entraînement avec navette Barrel et marche arrière. Bâti renforcé disponible.

Global® WF 904/905 Series

These WF 904/905 series are extra heavy duty walking foot machines, especially designed for sewing tents, bags and horse saddles. The large barrel shuttle hook offers high efficiency in heavy duty production.



WF 904 - Complete head and stand



WF 905-95 - Complete head and stand



WF 905 - Large barrel shuttle hook

Specifications

model	number of needles	stitch length up to	presser foot lift mm		max. sewing speed*	space to right of needle mm	needle system
			by hand	by knee			
WF 904	1	15	13	20	800	400	794 H
WF 905	1	11	13	20	800	400	794 H
WF 905-95	1	11	13	20	800	950	794 H

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL® Selection is brought to you by:

GLOBAL® is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:

- ① machine model
- ② part numbers